

Homework 5 – A Report on Iterative Techniques in Matrix Algebra

XIAOLONG LIU, 201900170025

22ed.Dec.2021

SHANDONG UNIVERSITY, TAISHAN COLLEGE

Abstract

In this report, we use Gaussian method and Cholesky decomposition and the Jacobi and Gauss-Seidel intertive method to compute x where $Ax = B$.

Contents

1	INTRODUCTIONS	2
2	ALGORITHM DESCRIPTION & MATHEMATICAL DERIVATION	2
2.1	GAUSSIAN METHOD AND CHOLSKY DECOMPOSITION	2
2.2	JACOBI AND GAUSS-SEIDEL INTERTIVE METHOD	2
3	CODES AND NUMERICAL EXPERIMENTS	3
3.1	GAUSSIAN METHOD AND CHOLSKY DECOMPOSITION	3
3.2	JACOBI AND GAUSS-SEIDEL INTERTIVE METHOD	5

1 INTRODUCTIONS

In this report, we use Gaussian method and Cholesky decomposition and the Jacobi and Gauss-Seidel intertitive method to compute x where $Ax = B$.

2 ALGORITHM DESCRIPTION & MATHEMATICAL DERIVATION

2.1 GAUSSIAN METHOD AND CHOLESKY DECOMPOSITION

We omitted these since these are just simply linear algebra.

2.2 JACOBI AND GAUSS-SEIDEL INTERTIVE METHOD

Theorem 2.2.1 (Jacobi). *Compute x with $Ax = b$ for x_i to obtain*

$$x_i = \sum_{j=1, j \neq i}^n \left(-\frac{a_{ij}x_j}{a_{ii}} \right) + \frac{b_i}{a_{ii}}, i = 1, \dots, n.$$

For each $k \geq 1$ and for $x^{(k)}$ we have

$$x_i^{(k)} = \frac{1}{a_{ii}} \left[\sum_{j=1, j \neq i} (-a_{ij}x_j^{(k-1)}) + b_i \right], i = 1, \dots, n.$$

Theorem 2.2.2 (Gauss-Seidel). *Compute x with $Ax = b$ for x_i to obtain*

$$x_i = \sum_{j=1, j \neq i}^n \left(-\frac{a_{ij}x_j}{a_{ii}} \right) + \frac{b_i}{a_{ii}}, i = 1, \dots, n.$$

For each $k \geq 1$ and for $x^{(k)}$ we have

$$x_i^{(k)} = \frac{1}{a_{ii}} \left[-\sum_{j=1}^{i-1} (a_{ij}x_j) - \sum_{j=i+1}^n (a_{ij}x_j^{(k-1)}) + b_i \right], i = 1, \dots, n.$$

3 CODES AND NUMERICAL EXPERIMENTS

3.1 GAUSSIAN METHOD AND CHOLESKY DECOMPOSITION

Problem 3.1.1. Given a equation $A\mathbf{x} = \mathbf{b}$ where $A = \begin{pmatrix} 100 & 2 & 4 & 7 \\ 2 & 100 & 5 & 19 \\ 4 & 5 & 100 & 5 \\ 7 & 19 & 5 & 100 \end{pmatrix}$ and $\mathbf{b} = \begin{pmatrix} 2 \\ 3 \\ 4 \\ 5 \end{pmatrix}$,

we will use the Gaussian method and Cholesky decomposition to compute \mathbf{x} .

Solution. Consider the following function:

```
1 >> format long
2 function x=GS(A,b)
3 [n,~] = size(A);
4 x=zeros(n,1);
5
6 for j = 1:n-1
7     for i = j+1:n
8         mul = A(i,j)/A(j,j);
9         A(i,:) = A(i,:) - mul*A(j,:);
10        b(i) = b(i) - mul*b(j);
11    end
12 end
13
14 for i=n:-1:1
15     sum=0;
16     for j=n:-1:i+1
17         sum=sum+x(j)*A(i,j);
18     end
19     x(i)=(b(i)-sum)/A(i,i);
20 end
21 end
22
```

And use the follows codes:

```
1 >> A = [100 2 4 7;
2         2 100 5 19;
3         4 5 100 5 ;
4         7 19 5 100];
5
6 b = [2;3;4;5];
7 >> GS(A,b)
8
9 ans =
10
11 0.015119617688382
12 0.019639842048166
13 0.036243328673106
14 0.043397890339006
```

Then $\mathbf{x} = \begin{pmatrix} 0.015119617688382 \\ 0.019639842048166 \\ 0.036243328673106 \\ 0.043397890339006 \end{pmatrix}$. Well done.

Now we will use Cholesky decomposition. Consider the follows function:

```

1 function [x,res]=CD(A,b)
2 AA=A; [n,n]=size(A);
3 y=zeros(n,1); x=zeros(n,1);
4 for k=1:1:n
5     A(k,k)=sqrt(A(k,k));
6     A(1:k-1,k)=0;
7     A(k+1:n,k)=A(k+1:n,k)/A(k,k);
8     for j=k+1:n
9         A(j:n,j)=A(j:n,j)-A(j:n,k)*A(j,k);
10    end
11 end
12 U=A'; L=A;
13 y(1,1)=b(1,1)/L(1,1);
14 for i=2:n
15     s=0;
16     for j=1:i-1
17         s=s+y(j,1)*L(i,j);
18     end
19     y(i,1)=(b(i,1)-s)/L(i,i);
20 end
21 x(n,1)=y(n,1)/U(n,n);
22 for i=n-1:-1:1
23     s=0;
24     for j=i+1:n
25         s=s+U(i,j)*x(j,1);
26     end
27     x(i,1)=(y(i,1)-s)/U(i,i);
28 end
29 res=norm(b-AA*x);

```

Then we have:

```

1 >> CD(A,b)
2
3 ans =
4
5     0.015119617688382
6     0.019639842048166
7     0.036243328673106
8     0.043397890339006

```

So $x = \begin{pmatrix} 0.015119617688382 \\ 0.019639842048166 \\ 0.036243328673106 \\ 0.043397890339006 \end{pmatrix}$. Well done. □

3.2 JACOBI AND GAUSS-SEIDEL INTERTIVE METHOD

Problem 3.2.1. We will use the Jacobi and Gauss-Seidel intertitive method to compute \mathbf{x} by construct \mathbf{A}, \mathbf{b} .

Solution. Use the following function to find \mathbf{A}, \mathbf{b} :

```
1 function [A,b]=DD(n)
2     T=zeros(n-1,n-1);
3     for i=1:n-1
4         T(i,i)=2;
5     end
6     for i=1:n-2
7         T(i,i+1)=-1;
8         T(i+1,i)=-1;
9     end
10    I=eye(n-1,n-1);
11    k=(n-1)^2;
12    A=zeros(k,k);
13    b=ones(k,1);
14    j=1;
15    for i=1:n-1
16        A(j:j+n-2,j:j+n-2)=T+2*I;
17        j=j+n-1;
18    end
19    j=1;
20    for i=1:n-2
21        A(j:j+n-2,j+n-1:j+2*n-3)=-I;
22        A(j+n-1:j+2*n-3,j:j+n-2)=-I;
23        j=j+n-1;
24    end
25 end
```

When we use the Gauss Seidel method, we use the following code.

```
1 function []=GSS(n,eps)
2     [A,b]=DD(n);
3     D=diag(diag(A));L=-tril(A,-1);
4     U=-triu(A,1);x=zeros((n-1)^2,1);k=0;maxit=100000;
5     B=(D-L)\U;g=(D-L)\b;
6     tic
7     while 1
8         k=k+1;
9         x=B*x+g;
10        res=b-A*x;
11        if norm(res,2)<eps
12            break
13        elseif k>=maxit
14            fprintf('The times to the maximum:\n');
15            break
16        else
17            continue;
18        end
19    end
20    toc
21 end
```

Then we have

```
1 >> GSS(25,1e-4)
```

```
2 0.079250
```

The jacobi's method as follows:

```
1 function []=JB(n,eps)
2   [A,b]=DD(n);
3   D=diag(diag(A));L=-tril(A,-1);U=-triu(A,1);x=zeros((n-1)^2,1);k=0;
4   maxit=100000;
5   B=inv(D)*(L+U);
6   g=inv(D)*b;
7   tic
8   while 1
9       k=k+1;
10      x=B*x+g;
11      res=b-A*x;
12      if norm(res,2)<eps
13          break
14      elseif k>=maxit
15          fprintf('The times to the maximum:\n');
16          break
17      else
18          continue;
19      end
20  end
21  toc
22  end
```

Then we have

```
1 >> JB(25,1e-4)
2    0.100129
```

Well done. □

References

- [1] Richard L. Burden, J. Douglas Faires, Annette M. Burden, *Numerical Analysis (Tenth Edition)*, Cengage Learning, 2014.